

IN THE CLAIMS:

Please amend the claims as follows:

- A
1. (Previously Amended) A procedure for the replicative fabrication and packaging of at least one microstructured molded part in form of one magazine/molded part composite, comprising the following process steps:
 - a. Replicatively fabricating at least one microstructured molded part using an initially closed tool which comprises at least one first and one second tool half;
 - b. Opening both tool halves, whereby the molded part remains in the first tool half;
 - c. Replacing at least the second tool half with at least one additional tool half;
 - d. Replicatively fabricating the magazine using the first tool half which contains the molded part and the additional tool half;
 - e. Simultaneously demolding the magazine and the molded part as one magazine/molded part composite.
 2. (Previously Amended) A procedure for the replicative fabrication and packaging of at least one microstructured molded part as one magazine/molded part composite, comprising the following process steps:
 - a. Replicatively fabricating the magazine using an initially closed tool which comprises at least one first and one second tool half;
 - b. Opening both tool halves, whereby the magazine remains in the first tool half;
 - c. Replacing at least the second tool half with at least one additional tool half;
 - d. Replicatively fabricating at least one microstructured molded part using the first tool half which contains the magazine and the additional tool half;
 - e. Simultaneously demolding the magazine and the molded part as one magazine/molded part composite.
 3. (Previously Amended) A procedure according to Claim 1, wherein at least one

microstructured mold insert is used for fabrication of the magazine and/or the molded part in the tool.

- a
4. (Previously Amended) A procedure according to Claim 1, wherein the molded part and the magazine is fabricated with different physical heights.
 5. (Previously Amended) A procedure according to Claim 1, wherein the magazine is fabricated with a lateral overhang in comparison to the horizontal dimension of the molded part.
 6. (Previously Amended) A procedure according to Claim 1, wherein the magazine is fabricated with a holding contact to parts of the side surfaces of the molded part.
 7. (Previously Amended) A procedure according to Claim 1, wherein the magazine is fabricated with a holding contact to the microstructures of the molded parts.
 8. (Previously Amended) A procedure according to Claim 1, wherein the magazine is fabricated with recesses.
 9. (Previously Amended) A procedure according to Claim 1, wherein the magazine is fabricated with a holding contact to the bottom or face surface of the molded part.
 10. (Previously Amended) A procedure according to Claim 1, wherein the magazine is fabricated with a holding contact to parts of the bottom or parts of the face surface of the molded part.
 11. (Previously Amended) A procedure according to Claim 1, wherein the molded part and the magazine are fabricated with the same or with different mold materials.
 12. (Previously Amended) A procedure for the replicative fabrication and packaging of at least one microstructured molded part as one magazine/molded part composite,

comprising the following process steps:

- a. Replicatively fabricating at least one microstructured molded part using a prefabricated magazine;
- b. Simultaneously demolding the magazine and the molded parts as one magazine/molded part composite.

13. (Previously Amended) A procedure according to Claim 12, wherein a split tool is used which comprises at least one first and one second tool half.

14. (Previously Amended) A procedure according to Claim 12, wherein a prefabricated magazine is used after removal of the microstructured molded parts.

15-24 Cancelled

25. (New) A procedure according to Claim 2, wherein at least one microstructured mold insert is used for fabrication of the magazine and/or the molded part in the tool.

26. (New) A procedure according to Claim 2, wherein the molded part and the magazine is fabricated with different physical heights.

27. (New) A procedure according to Claim 2, wherein the magazine is fabricated with a lateral overhang in comparison to the horizontal dimension of the molded part.

28. (New) A procedure according to Claim 2, wherein the magazine is fabricated with a holding contact to parts of the side surfaces of the molded part.

29. (New) A procedure according to Claim 2, wherein the magazine is fabricated with a holding contact to the microstructures of the molded parts.

30. (New) A procedure according to Claim 2, wherein the magazine is fabricated with recesses.

31. (New) A procedure according to Claim 2, wherein the magazine is fabricated with a holding contact to the bottom or face surface of the molded part.

32. (New) A procedure according to Claim 2, wherein the magazine is fabricated with a holding contact to parts of the bottom or parts of the face surface of the molded part.

33. (New) A procedure according to Claim 2, wherein the molded part and the magazine are fabricated with the same or with different mold materials.

34. (New) A procedure according to Claim 13, wherein a prefabricated magazine is used after removal of the microstructured molded parts.